

ShaliPrime® WB

Acrylic Polymerized Mastic Water Based Primer



Description

ShaliPrime® WB is an acrylic polymerized, anti-root, water-based primer designed to provide better adhesion for any coatings. **ShaliPrime® WB** has good alkali resistance properties.

Characteristics

Colour	White	Flash Point, °C	Non-flammable
Drying Time, hrs.	2	Solid content, %	44 ± 2
Theoretical coverage*, Kg/ m ²	0.20-0.25	Specific Gravity	1.32 ± 0.02

* Depending upon surface condition.

Application

As a primer for subsequent application of topcoat/liquid applied membrane for exterior or interior finish.

Advantages

- Easy to apply.
- Excellent hiding property.
- Fast Drying.
- Anti root
- VOC Free

Application Methodology

➤ Surface Preparation

- Remove all loose gravel, dirt, oil, grease and foreign matter by jet of dry air and clean the surface mechanically or by grinding to make it smooth before application.
- For previously painted surface, ensure all peeled off or flaked paint is removed.
- Dust down the entire surface.

➤ Application of Material

- Stir well before application.
- Apply **ShaliPrime® WB** at the rate 0.20-0.25 Kg/m².
- Apply uniform coat of **ShaliPrime® WB** with brush, roller or by spraying.
- Do not apply **ShaliPrime® WB** when humidity is over 90% or when ambient temperature is not above 3°C of dew point.
- Check the surface moisture content (should be less than 4%) before application of **ShaliUrethane LHM** on **ShaliPrime® WB**.

Health & Safety

- Avoid contact with skin / eyes and avoid swallowing.
- Ensure adequate ventilation and avoid inhalation of vapor.
- Wear suitable protective clothing, gloves and eye protection.
- In case of contact with skin, rinse with plenty of clean water, then cleanse with soap and water. Do not use solvent to clean the contacted area.
- In case of contact with eyes, wash immediately with plenty of clean water and seek medical advice.
- If swallowed, seek medical attention immediately. Do not induce vomiting.
- Dispose of empty container as per local rules.

Packing

Available in 25 kg bucket.

Storage

Keep in cool and dry place, in air tight containers, under shed, away from heat.

Shelf Life

12 months in unopened air tight condition.



- Product Range**
- Waterproofing & Insulation
 - Sealants & Adhesives
 - Protective/Anti-Corrosion Coatings
 - Grouts and Admixtures (GARA)
 - RestoFix - Repair/Rehabilitation
 - Road Surfacing
 - Pipeline Coatings
 - Epoxy and Flooring
 - Other Construction Chemicals



Advisory Cell: +91 81302 81114

www.stpltd.com