

SILK METALLICS



Product Attributes

Brilliant
Metallic Sheen



UV Protect &
Colour Retention

Tintable Shades



Green Pro
Certified

Low VOC



Interior &
Exterior Use

Product Description:

Elevate your walls with the brilliance of Silk Metallics. This premium water-based paint, featuring a 100% acrylic emulsion, provides a beautiful metallic shade and a durable finish. Its versatility allows application in both interior and exterior surfaces, ensuring a shiny statement that lasts across any space.

Recommended Use:

Areas of application:



Metal



Wood



Masonry

Suitable for:



Interior & Exterior

Colour Range:



Gold, Silver.
Tintable shades.

Finish:

Gloss

Hi-Gloss

Super Gloss

Metallic Sheen

Dilution Ratio:



200 ml water per 1 litre
of Metallics for
roller/brush application.
No dilution for design

Coverage:



Direct application-
130-150 SQ.
FT./LTR./COAT*

*Coverage may vary due to factors
such as application methods,
nature of substrate, conditions etc.

Application Method:



Brush, Roller & Spray

Gloss Level:



Metallic Luster Finish

Drying Time:



Surface dry: 1 hour
Hard dry: 6-8 hours



SILK METALLICS



Packs Available



200ml

1L



Fire Hazard Class
Non- flammable



Shelf Life

Best before 36 months from date of manufacture when stored in a properly sealed container at room temperature.



Shades
Gold and Silver

Surface Preparation On Previously Painted Surfaces:

Interior Walls:



Strip the old paint and all the loose particles from the surface and wipe down.



Sand it with emery paper 80/100 and wipe clean.



Apply the first coat of primer and let it dry for 6 to 8 hours.



Smoothen the surface by applying thin coats of Silk Acrylic putty (No dilution) to fill in all the gaps. Let the putty to dry overnight.



Sand the surface again, with emery paper 200/220, and wipe clean.



Apply the second coat of primer and let it dry for 6 to 8 hours. Sand the surface with emery paper 320 and wipe clean.

Exterior Walls:



For new masonry, it should be allowed to cure completely.



For old painted surface, ensure the surface is free from loose paints, dust, grease, microbial growth etc.. by sanding or wire brushing followed by cleaning with water jet.



Cracks, holes, dents, damp areas etc. should be repaired properly before painting. Treat the surface with Biowash solution and wash it next day with potable water and let the surface to dry completely (moisture content).

Directions of Application:

1. Ensure the surface is clean, dry, and free from loose particles before application.
2. Apply one coat of Seal-O-Prime as the base coat.
3. Use Parrot Wood Primer for wooden surfaces and QD Epoxy Primer for metal surfaces.
4. Once the primer is fully dry, apply two coats of Silk Metallics, allowing 4-6 hours of drying time between each coat for best results.

Points to Note:

- Stir well and strain before use.
- Do not apply when ambient temperature is below 100°C.
- Recoat and drying of paint are tested at 30±2°C and 60-65% RH. These may vary under different conditions.
- Fire Hazard Class: Non-Flammable.
- Tint with Berger Paints colorants only to get desired shade from Berger Shade card.
- Keep the container tightly closed in cool and dry place.
- Please keep it out of reach of children and away from foodstue.
- In case of contact with eyes, wash immediately with water and seek medical.

Version No: BPP1/06/2025. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 • CONSUMER RELATIONS MANAGER • Ph: 1800-103-6030
SMS BERGER to 56767 • Email: consumerfeedback@bergerindia.com • www.bergerpaints.com
Corporate Office: Plot No. : CF - 4 • Premises No. : 02-0173 • Action Area - IC • New Town • Kolkata 700 156