

# EASY CLEAN SILKY TOUCH

Washable Luxury Interior Emulsion



## USP



**Silky Smooth  
Finish**

**Unmatched  
Washability**



**Anti-Bacterial**

**Flexible  
Paint Film**



**Anti  
Fungal**

## Product description

**Easy Clean Silky Touch**, a technologically advanced product with a perfect blend of functionality and aesthetics. Its specially curated silky wax gives the walls a smooth finish and the cross-linking polymers make it stain-resistant and washable. Make your walls stain-free, beautiful and silky smooth with Easy Clean Silky Touch.

## Recommended Use

Plastered surfaces, concrete walls, fibre board, asbestos, gypsum board and false ceiling.

## Coverage



120-130 sqft/ltr/2 coats depending on shade, quality of surface preparation and application condition.



## VOC

50 gm/ltr (max)

## Recommended Dilution




Brush application: 40-50% by volume.  
Auto-roller/ spray: 35-50% by volume.  
Deep shades from the N2 base are to be applied without dilution

## Drying Time



Surface Dry: 15-25 min at 60% RH, 25°C  
Hard Dry: 6-8 hours

## Gloss/Sheen




10 @ 60° minimum

## Stability of used paint



Use within 24 hours

## Application Tools



Xpress Painting Tools such as Auto-roller, spray etc.

## Application Tools



Water-based paint, hence non-flammable

# EASY CLEAN SILKY TOUCH

Washable Luxury Interior Emulsion



## Packs



1 Ltr      4 Ltr      10 Ltr      20 Ltr

### ColorBank

Pack of 0.9, 3.6, 9 & 18 L

### Bases

P1, N2, Yellow & Red




**Fire Hazard Class**  
Non- flammable



**Pot Life of Thinned Material**  
Overnight

## Surface Preparation



For fresh/ new surfaces, ensure the surface is clean and dry and free from all loose particles, chalk, grease, fungus and algae. Sand the surface with Emery Paper No. 80 and wipe clean.




Cover fine cracks with putty, large cracks may need cement work. Allow sufficient time for the putty / cement to dry.



Apply the first coat of primer and allow it to dry for 6 – 8 hours.



Smoothen the surface by applying thin coats of putty to fill in all the dents. Allow the putty to dry overnight.



Sand the surface with Emery Paper No. 100 and wipe clean. Apply the second coat of primer and allow it to dry for 6 – 8 hours. Sand the surface with Emery Paper No. 220 and wipe clean.

**For Previously Painted Surfaces:** Strip the old paint as far as possible. Roughen the unremoved portion with no 180 or no 220 emery paper. Remove all loosely adhering particles or dust.

## Directions for Application

For topcoat, dilute the paint as per the recommended dilution ratio. Apply the first finishing coat with brush or roller and allow it to dry for at least 6 -8 hours. After the first coat dries, apply the second coat and allow it to dry overnight.

### Cleanability

Before cleaning, let the paint film form properly for minimum 28 days. To clean the stains, apply mild liquid soap solution (turpentine can be used for oil based stains) and wipe clean.

### Points to Note

- ▶ Shake well before use
- ▶ Do not over dilute.
- ▶ Keep the container tightly closed to prevent drying
- ▶ Use one coat of Bio – Wash for killing fungal growth
- ▶ Scrape off old paint thoroughly before painting starts
- ▶ Gyro shake well after tinting through CB Machine
- ▶ For deep shade apply one additional coat
- ▶ Do not apply paint on lime washed surfaces and damp wall
- ▶ In case of contact with eyes, wash immediately with water and seek medical help
- ▶ Do not apply paint when ambient temperature is below 10° C or above 45° C

Version No: BPP1/03/2024. Please note that this data sheet supersedes all previous versions.

## BERGER PAINTS INDIA LIMITED

**Berger House**, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030  
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: [consumerfeedback@bergerindia.com](mailto:consumerfeedback@bergerindia.com) | [www.bergerpaints.com](http://www.bergerpaints.com)