

RANGOLI RICH MATT



Product Attributes



Rich Matt Finish

Superior Hiding



Superior Whiteness

Superior Coverage




Product Description

Rangoli Rich Matt is a water based 100% acrylic emulsion with 100% Matt Finish along with superior hiding & coverage. It gives a smooth and durable finish which is tintable in wide range of colors.

Recommended Use


Plastered surfaces, concrete walls, fiberboards, asbestos, gypsum boards and false ceilings.

Colour Range



Over 2,000 shades

Finish



Premium Rich Matt Finish

Toxicity



Non Toxic

Coverage



100 -120 sqft. / Ltr / 2 coats, under ideal test conditions.

(Coverage may depend on factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc.)

Recommended Undercoats

Primer: BP Cement Primer (W/T) or BP White Primer or Walmasta 2-in-1 Interior- Exterior Primer can be used

Putty: For wall/ plastered surfaces – Bison Wall Putty/ Happy Wall Putty

Gloss Level



60° = less than 4

Anti - fungal



Resists growth of algae, fungus and moulds

Drying Time



SD: 15 -25 min at 60% RH , 25° C

HD: 6 - 8 hours

Application Method



Brush/ Roller/ Spray

Dilution Ratio



50% by volume

Recommended Thinner



Potable water

RANGOLI RICH MATT



Packs



1 Ltr

4 Ltr

10 Ltr

20 Ltr




Fire Hazard Class
Non- flammable



Pot Life of Thinned Material
Overnight

Surface Preparation



For fresh/ new surfaces, ensure the surface is clean and dry and free from all loose particles, chalk, grease, fungus and algae. Sand the surface with Emery Paper No. 80 and wipe clean.




Cover fine cracks with putty, large cracks may need cement work. Allow sufficient time for the putty / cement to dry.



Apply the first coat of primer and allow it to dry for 6 – 8 hours.



Smoothen the surface by applying thin coats of putty to fill in all the dents. Allow the putty to dry overnight.



Sand the surface with Emery Paper No. 100 and wipe clean. Apply the second coat of primer and allow it to dry for 6 – 8 hours. Sand the surface with Emery Paper No. 220 and wipe clean.

For Previously Painted Surfaces: Strip the old paint as far as possible. Roughen the unremoved portion with no 180 or no 220 emery paper. Remove all loosely adhering particles or dust.

Directions for Application

For topcoat, dilute the paint as per the recommended dilution ratio. Apply the first finishing coat with brush or roller and allow it to dry for at least 6 -8 hours. After the first coat dries, apply the second coat and allow it to dry overnight.

Points to Note

- Shake well before use
- Do not over dilute.
- Keep the container tightly closed to prevent drying
- Use one coat of Bio – Wash for killing fungal growth
- Scrape off old paint thoroughly before painting starts
- Gyro shake well after tinting through CB Machine
- For deep shade apply one additional coat
- Do not apply paint on lime washed surfaces and damp wall
- In case of contact with eyes, wash immediately with water and seek medical help
- Do not apply paint when ambient temperature is below 10° C or above 45° C

Version No: BPP1/07/2023. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com