

Product Code 941004



One Pure Legend

The ultimate luxury paint with PU (Polyurethane) that gives Outstanding Crack Protection

PRODUCT FEATURES AND BENEFITS*



Outstanding Crack bridging

Prevents hairline cracks and fine shrinkages on walls to maintain new look for longer.



Excellent Scuff Resistance

Resists furniture drag marks to ensure long lasting beauty.



Softest Touch and Feel

Provides feathery soft touch and luxurious feel for your walls.



Anti-Bacterial

Kills 99.9% bacteria.



Other Features

1. Ultra High Sheen
2. Excellent Stain Resistance
3. Effective water beading
4. Anti-Fungal
5. High Spatter Resistance
6. Great Washability
7. Easy and Fast Application
8. Roller friendly paint
9. Ultra Low Odour & VOC

PRODUCT DETAILS



HIGH SHINE FINISH

COVERAGE

140-160 sq ft/L for 2 coats

Only on non-porous surface with correct surface preparation using recommended primer and with correct deposition.



Actual coverage may change from the mentioned coverage depending on the method of application and surface condition.

2300+ SHADES* AVAILABLE
PACKS AVAILABLE



AVAILABLE BASES

Pastel, Mid Tone, Clear, Red and Yellow

PROCESS TO APPLY (PRE-PAINTING STEPS)

Plaster




New masonry surfaces must be allowed to cure completely. The recommended curing period is 28 days for new masonry surfaces while ensuring that they are water cured on a daily basis.

Dampness



The moisture level for any surface that is to be painted should be below 16%. Post checking for dampness, appropriate treatment of the damp surface should be carried treating the fundamental cause for the dampness.

Cleaning




The surface should be cleaned for any presence of loose paint, dust, or grease. Growth of fungus, algae or moss should be removed by wire brushing and water or by bio-wash. When the underlying surface exhibits chalkiness, please use water curing for some time and then apply a layer of Birla Opus One Pro Smooth Primer before topcoat application.

Cracks



Fill surface cracks of up to 5 mm width & 3 mm depth using Birla Opus Alldry Crack Master, applied as per instructions given in the latest PIS before further steps. Loose plaster, structural cracks, etc. need to be treated as per standard construction practices.



Sanding

Allow the freshly plastered surface to cure completely. Remove loose paint, dust dirt etc. with sandpaper no. 180 and wipe the surface clean.



Primer Application

Apply one coat of Birla Opus One Pro Smooth Primer or equivalent Birla White interior Primer. The primer should be mixed with water in the recommended ratio. After the application ensure a drying time of 6 hours.



Putty Application

Smoothen the surface by filling undulations with 2 coats of Birla Opus One Pro Smooth Putty or equivalent Birla White interior Putty. Allow it to dry for 4-6 hours between successive coats. Apply third coat of putty if required and then sand with sandpaper no. 320, and wipe the surface.



Primer Application


Apply 1 coat of Birla Opus One Pro Smooth Primer or equivalent Birla White interior Primer and allow it to dry for 4-6 hours. Sand the surface using sandpaper no. 400, post which wiping the surface will be required.



Topcoat Application

Use 1L paint mixed with 400-500 ml of water and apply 2-3 coats by using brush followed by foam roller for optimal results. The time between successive coats should be 4-6 hours.

PROCESS TO APPLY (POST-PAINTING CARE)



- Ensure dry dust cleaning at regular intervals.
- While cleaning, wipe gently without intense pressure.
- Give 2 weeks of drying time post application of paint before wet-cleaning the wall.
- Use 5% detergent solution to clean stains from the wall using a soft cotton cloth or sponge. Stains are best removed within 4 hours.

TECHNICAL INFORMATION

Shelf-Life: 36 months

Drying Time: Surface dry time 30 minutes*

*May vary according to temperature and humidity.

Sheen Levels (on glass plate): 30-45* at 60 deg GH*

*as per recommended internal test method and conditions.

Volatile organic compound (VOC)

level in all bases <25 gm/l

Flash point IS101/1987 Part 1, Sec 6: Not Applicable

Stability of thinned paint: To be used within 24 hours.

Recoating Time: 4-6 hours after the first coat.

SAFETY ASPECTS

- Do not apply when ambient temperature is below 10°C or might drop to a level below this within 4 hours of application
- Do not apply if humidity > 90%
- Wear dust mask during application, sanding, and cleanup.
- Do not over-thin or over-extend the brush.
- Stir well and strain before use.
- New plaster should be allowed to cure for minimum 28 days.
- Ensure adequate ventilation during application and drying.
- Avoid prolonged or repeated contact with eyes. In case of contact with eyes, rinse immediately with a plenty amount of water, and seek medical advice.
- Refrain from disposing leftover paint down the drain or in water bodies.
- Lead content does not exceed more than 90 parts per million.
- No added Mercury, Chromium, and Arsenic compounds.

Softest Touch & Feel

- Against players in the same product category, basis internal lab tests.

Anti-Bacterial

- As per in-house microbiology test report (As per JIS Z 2801) & anti-bacterial testing certified by Biotech Testing Services Labs, Mumbai. It kills 99.9% of Staphylococcus aureus, Escherichia coli & Pseudomonas aeruginosa bacteria.

Anti-Fungal

- As per Anti-Fungal Chamber Test Method.

Ultra High Sheen

- Against players in the same product category, basis internal lab tests.

Ultra Low VOC

- As per in-house test report (test method- ASTM D6886:2018)

Shades

- Shades may vary with wall and light conditions. Availability of shades may differ. Consult your nearest authorised dealer to determine availability.

***All the comparison has been made for the respective white base only"

For further details, please reach out to our customer care via either of the following methods:
Contact number: 1800-120-1234, Email ID: opuscare@adityabirla.com